



X-09™ High Security Lock



X-09™ Features



Meets FF-L-2740A

Make your safe the safest with the X-09, electromechanical lock. Approved by the GSA for use on approved Class 5 and Class 6 filing cabinets and Class 5 and Class 8 Security vault doors. The X-09 is self-powered using PowerStar™ technology (an internal self-activating power-plant), and features a limited view LCD display.

A twist of the dial provides all the power necessary to enter the combination, as well as review audit features. The X-09 provides all of the benefits of high-security electronic locking while maintaining the reliability of a mechanical lock, independent of batteries or outside power sources. It's security with a twist.

Since the X-09 isn't subject to mechanical limitations, it provides a far superior solution for your container needs. Advanced engineering assures that X-09 entry codes can not be compromised by observing the dial position. Plus, the tamper-resistant X-09 can not be "hacked" because the digital information is hidden in the processor's non-volatile memory.

Representing a giant step forward in controlled access, the X-09 features multiple modes of user access, and audit features. These user-friendly locks provide virtually maintenance-free operation and features Kaba Mas's exclusive PowerStar™ technology.

X-09™ Applications



X-09™ Applications

We've integrated the X-09 technology with a rim deadbolt platform to represent a unique and complete high security door lock solution while complying with most safety requirements. Along with the X-09, the combination door lock unit is added to form the CDX-09 which allows you to have access control on any door. The CDX-09 conforms to FF-L-2890.



High Security Pedestrian Exit Device*

Kaba Mas has configured the X-09 in ways that fit your specific applications. We've mated the CDX-09 with both a mechanical fire rated exit device or an electronic latch retraction fire rated exit device (for use with your card reader or other input device). In either application, the modified CDX-09 is interconnected with the exit device releasing the deadbolt and the latchbolt when the touch bar is depressed.

Three Modes of Operation

Choose your level of operation. **The Single Combination Mode** allows access by dialing a six-digit combination. **The Dual Combination Mode** allows access only when two separate codes are entered within 10 seconds of one another. **The Supervisory/Subordinate Mode** allows access by a subordinate only after a supervisor code has been entered.

Audit Feature

The X-09 has a full compliment of auditing features, including non-resettable openings log, and unsuccessful attempts log (audits after 3 unsuccessful attempts) that resets once the proper access code is entered.

PowerStar™ Technology

The X-09 feature our exclusive PowerStar™ technology which generates its own electrical energy with each turn of the dial. No batteries, wires or hassles. it's electronic access control - with a twist.

X-09™ Specifications

Hardware Specifications

Power:	Internal, self-powered by PowerStar™ technology.
Combinations: 3 modes:	
Single:	1 million combinations
Dual:	500 billion combinations
Supervisor/Subordinate:	2 million combinations
Direct Dial:	No need to clear before entering combination. Once you stop turning the dial, the power will shut down after 40 seconds.
Dead Zones:	None
Memory:	Non-volatile
LCD:	Limited View Liquid Crystal Display with indicator arrows makes dialing easy and exact.
Combination Changes:	LCD indicators in change key mode. Combination changed with correct combination or serial number.
Random Number View:	True Scramble
Daylocking:	No
Back Dialing:	No
Lock Reset:	Automatic when bolt is thrown or 40 seconds after turning has stopped.
Manipulation:	Fail secure against high-voltage attack, robot attack, X-ray methods, magnetic, vibration, and R/F.
Audit:	The X-09 records all openings and the record is non-resettable. The X-09 records unsuccessful attempts after 3 incorrect combination attempts and resets after a correct opening.
Wrong Try Penalty:	10-14 errors results in a 3 minute time out. 15 errors or greater results in a 4 minute time out. Both error count and penalty time resets with valid combination.
Back Cover:	Lock on back cover pin prevents removing the back cover without the combination.

Environmental Performance

Temperature:	Tested -10°F to 155°F Operational Range.
Salt Spray:	Operational After 72 hours of continuous exposure (per ASTM B117-90).
High R.P.M.:	Not operational after 4 hours in each direction @ 600R.P.M. Fails Secure.
Cycle Test:	Meets or exceeds FF-L-2740A specifications.
Humidity:	Operational after 10 days of 140°F @ 98% humidity (Operational after 10 days testing per MIL-STD-810E, Method 507.3, Procedure III, Temperature Cycling 86°F to 140°F @ 98% RH)
Stress:	Operational after 7 days in a stress chamber @ 194°F. Meets FF-L-2740A Specification.
Vibration:	MIL-STD-810
Shock:	MIL-STD-901
Electrical Discharge:	250KV on Dial
Electromagnetic Pulse:	Meets FF-L-2740A specification for simulation of high altitude nuclear blast.
Case & Bolt Strength:	600 pounds in two directions.



IMPORTANT NOTE:

Department of Defense and Agencies - Inquiries please contact:
Naval Facilities Engineering Service Center
Security Engineering Division • DoD Lock Program
Port Hueneme, CA 93043-4370 • Phone: (805) 982-1574
Fax: (805) 982-2444 • <http://locks.nfesc.navy.mil/>



Your Total Access Partner



Mechanical Locks

Kaba Mas offers a full line of mechanical combination Locks, Dial and Ring sets, as well as, Safe Deposit locks and Hinges. Our Dial and Ring sets are available in Black and White, Satin Chrome and Bright Brass finishes.



Kaba LC Series

The Kaba LC Series PowerSaver™ managed locks takes a battery for all it's worth... and then some. The new Low Current battery lock from Kaba comes with our exclusive spindleless slide bolt and features multiple user capability. Choose from the lexan (LCLX) or metal (LCMX) housings.



Auditcon Lock Series

The Auditcon® family of electronic locks has been developed specifically for today's business environment - addressing the requirements of a broad range of retail, commercial and industrial markets. Auditcon's security cannot be compromised by outside manipulation and provides unprecedented audit capability, making it the most effective deterrent to internal theft... ever.

Contact Information

Kaba Mas

Additional Product Information, Marketing, Education and Sales, Customer Service and Technical Support can be found on the web at www.kaba-mas.com/contact.html

Kaba

For more information on the Kaba family of products, visit us at <http://www.kaba.com/index-e.html>

Kaba Mas Corporation

749 W. Short St.
Lexington, KY 40508 USA
phone 859-253-4744
toll-free 888-950-4715
fax 859-255-2655
web www.kaba-mas.com
info www.kaba-mas.com/contact.html

